

NEW High Quality Stainless Steel Interior and Countertop



FEATURES / BENEFITS

- EFFICIENT REFRIGERATION SYSTEM**
 Turbo Air refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.
- FORCED AIR COOLING SYSTEM**
 Fast cooling and balanced temperature throughout the cabinet.
- STAINLESS STEEL CABINET CONSTRUCTION**
 This model boasts a stainless steel interior and counter top. It guarantees the utmost in cleanliness and long product life. The Back Bar can add a touch of style to the most refined setting.
- HIGH-DENSITY POLYURETHANE INSULATION**
 Entire cabinet structure is formed-in-place using high density, CFC free polyurethane insulation.
- FLUORESCENT INTERIOR (SG MODEL ONLY)**
 Bright fluorescent interior lighting is specifically designed for perfect visibility throughout the interior.
- ADJUSTABLE, HEAVY DUTY, PE(POLYETHYLENE) COATED WIRE SHELVES**
- TRIPLE GLASS**
 Triple pane thermal glass provides extra ability to maintain cool temperatures.
- ERGONOMICALLY DESIGNED DOORS**
 Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.
- SIDE MOUNT COMPRESSOR UNIT**
 Through positioning the compressor to the side, the refrigerator can be serviced without being moved. By innovatively creating a front breathing feature, this model can provide high efficiency in narrow spaces.
- INCANDESCENT INTERIOR LIGHTING**
- REFRIGERATOR HOLDS 33°F ~ 38°F FOR THE BEST IN BEVERAGE PRESERVATION**

| Model | Swing Door | CU./FT. | 1/2 Barrels | #of Shelves | HP | AMPS | Crated Weight | L D H |
|------------|------------|---------|-------------|-------------|-----------|------|---------------|-----------------------|
| TBB-1SD/SB | 1 | 8.3 | 1 | 2 | 1/4 | 4 | 235 | 235/8 x 293/4 x 405/8 |
| TBB-2SG/SB | 2 | 19 | 2 | 6 | 1/3 - 1/4 | 7 | 344/332 | 583/4 x 271/4 x 371/8 |
| TBB-3SG/SB | 2 | 23 | 3 | 6 | 1/3 - 1/4 | 7 | 385/369 | 69 x 271/4 x 371/8 |
| TBB-4SD/SB | 3 | 33.2 | 4 | 8 | 1/3 | 7 | 465/480 | 903/8 x 271/4 x 373/8 |
| TBB-4SG | 3 | 33.2 | 4 | 8 | 1/2 | 9 | 545 | 903/8 x 271/4 x 373/8 |

* Height does not include 6" for caster height. * Depth does not include 1" for door handle (SG Models). * Depth does not include 1-1/4" for rear spacers.

TBB MODELS SPECIFICATIONS

| MODEL | TBB-1SD/SB | TBB-2SG/SB | TBB-3SG/SB | TBB-4SD/SB | TBB-4SG |
|----------------------------|--|--|---|--|--|
| Exterior Dimension (LxDxH) | 23 ⁵ / ₈ x29 ³ / ₄ x40 ⁵ / ₈ | 58 ³ / ₄ x27 ¹ / ₄ x37 ¹ / ₈ | 69x27 ¹ / ₄ x37 ¹ / ₈ | 90 ³ / ₈ x27 ¹ / ₄ x37 ¹ / ₈ | 90 ³ / ₈ x27 ¹ / ₄ x37 ¹ / ₈ |
| Cubic Feet(Half Barrels) | 8.3 | 19 | 23 | 33.2 | 33.2 |
| Compressor (HP) | 1/4 | 1/3-1/4 | 1/3-1/4 | 1/3 | 1/2 |
| # of Shelves | 2 | 6 | 6 | 8 | 8 |
| Net Weight | 190 lbs | 276 lbs / 286 lbs | 298 lbs / 308 lbs | 435 lbs | 442 lbs |
| Voltage ⓘ NEMA-5-15P | ⓘ 115/60/1 | ⓘ 115/60/1 | ⓘ 115/60/1 | ⓘ 115/60/1 | ⓘ 115/60/1 |
| Amp | 4 | 7 | 7 | 7 | 9 |
| Cord Length (ft) | 9 | 9 | 9 | 9 | 9 |
| Plug-In | NEMA 5-15P | NEMA 5-15P | NEMA 5-15P | NEMA 5-15P | NEMA 5-15P |

*Design and specifications subject to change without notice.

■ **WARRANTY :** 1 Year Labor and Parts Warranty
Additional 4 Years Warranty on Compressor

- **SELF-CONTAINED SYSTEM**
- **DOOR LOCKS STANDARD (SB MODEL ONLY)**
- **4" SWIVEL CASTERS**
- **REMOTE CABINETS AND CONDENSING UNITS AVAILABLE FOR ALL MODELS.**

(unit : inch)

